

# Full HD 1080p

High Definition video over coaxial cable



# **Business** - SERIES

# **AHD 1080P HIGH DEFINITION CCTV SOLUTIONS**

#### 2.4 Megapixel Weatherproof 30 Meters IR Camera

- 1/2.9" SONY Exmor CMOS sensor
- True Day / Night with built in ICR
- Minimum illumination Color Mode: 0.0001 Lux B/W Infrared Mode: 0 Lux
- 3.6mm HD 3.0MP wide angle IR camera lens
- Max. 30 meters IR range (99 ft.)
- 36 pcs. x BLACK DIAMOND IR LED's
- Cable-thru mounting bracket
- OSD (On Screen Display) menu setup
- Power Input : 12VDC
- IP rating: IP67
- Epoxy powder coated housing & bracket











# **Double** surge protection inside

Built in with double TVS (Transient voltage suppressor) & ESD (Electrostatic discharge) surge protection against nearby lightning strikes on air that creates minor surge to the camera



#### Surge protection 1

Main dedicated surge protection board module



Surge protection 2
Surge protection circuit
built-in main camera board

#### TECHNICAL SPECIFICATIONS

#### Model: A36

IMAGE SENSOR VIDEO RESOLUTION VIDEO OUTPUT

MINIMUM ILLUMINATION

CAMERA LENS TYPE

TRUE DAY/NIGHT INFRARED DISTANCE INFRARED LED

SCANNING SYSTEM S/N RATIO WHITE BALANCE GAIN CONTROL ELECTRONIC SHUTTER

OPERATIONAL TEMP.
OPERATIONAL HUMIDITY
POWER SUPPLY INPUT
OPERATING CURRENT

CASING CONSTRUCTION FRONT GLASS DESIGN CAMERA NETT WEIGHT

- 1/2.9" SONY Exmor CMOS sensor
- 1080p (1920 x 1080)
- AHD or CVBS (selectable)
- Color mode: 0.0001 Lux
- B/W IR mode: 0 Lux (IR On)
- 3.6mm HD 3.0 megapixel fixed iris lens (optional 6mm)
- Yes, built in ICR inside
- Max. 30 Meters / 99 ft.
- 36 units x BLACK DIAMOND IR LED's
- Progressive scan
- More than 50db (AGC off)
- Selectable ATW / AWB / Manual
- Selectable Auto / Flicker / Manual - PAL: 1/50 ~ 1/100000
- NTSC: 1/60 ~ 1/100000
- 0°C ~ 60°C
- Within 85% RH
- DC12V
- 50mA (IR Off) / 340mA (IR On)
- Aluminum die-cast
- Anti IR reflect
- Approx. 400 grams

## Smart IR auto dim control

Eliminates object from over exposure caused by strong IR illumination during night. Furthermore, SMART IR exposure level can be program accordingly to installation scenes. Example: Distance between object & the camera







SMART IR (Night / IR On) Non exposure video

### **0.0001Lux** low illumination

Excellent low lighting capabilities, INOX AHD cameras continue to produce brighter & clearer with 95% noiseless color video quality even in low lighting installation scenes compare to others (IR off mode)



Others



INOX AHD camera - 0.0001 Lux 95% noiseless color night mode

# **2D + 3D** digital noise reduction

Reduces 95% of video noise during low lighting or night scenes. Cameras with 2D + 3D DNR function produces smoother & clearer video compare with conventional cameras without 2D + 3D DNR



Without 2D + 3D DNR



With 2D + 3D DNR Smooth & clear video during nigh

# OSD menu setup

Easy camera setup accordingly to installation scene conditions and lighting with the built-in OSD menu control on the camera





## **MOTION** screen alert

Supports 4x programmable motion preset area to detect motion movements. A useful function to alert users for intruders in the restricted zones when monitoring multiple screens at the same time



Without motion detect alert



With motion alert ON Easier to notice in dark area

# **DWDR** dark spot remover

Clearer and more detail video images. DWDR eliminates dark shadow areas in the video produced by the camera. This function is extremely useful for installation scenes that contain both bright and dark areas





Without DWDR

DWDR On

Manufactured & distributed by;

#### INOX MANUFACTURING (M) SDN. BHD.

- Malaysia (Company No. 671850-H)

#### **INOX SECURITY PTY. LTD.**

- Canada (Incorporation No. BC0722077)



www.inox.com.mv



Authorised Dealer:

Specifications, description and design are subject to change without prior notice. All pictures used in this brochure are for illustration purpose only. The brands and products names are properties of their respective owners